

FLEXIROL 500

For top hung sliding timber and metal doors. Max. 500kg.

APPLICATION

- Ideally suited to hotels, conference centres, shop fronts, showrooms or any site requiring high performance and an attractive finish
- Designed for straight sliding doors in timber, metal or glass

DOOR SPECIFICATION

Track System **Flexirol 500**

For Individual Doors:

Max Door Weight 500kg. 2 Hangers per leaf.

Max Door Width 6000mm

Door Thickness 40-100mm*

Max Door Height 6000mm

* For doors thicker than 100mm, please contact our technical sales team for further information.

HARDWARE SPECIFICATION

Track **H550** Anodised Aluminium (2000, 3000, 4000 & 6000mm lengths)
For full range of finishes please contact our Technical Sales Team.

Brackets **H1A/550** Face fixed
H3S/550 Soffit fixed


Hangers **H556** Metal doors - angle frame fixing
(2 per door)* H556/52 Timber doors - angle plate fixing
H556/57 Timber doors - concealed plate fixing

* Each panel must be rigid enough to be supported by only two hangers


Track Stop **H3/301** Flexirol track stop

Guides **H104N/94** Metal doors - angle frame fixing
H104NX/94 Metal doors - box frame fixing
H106HSS/94 Timber doors - concealed fixing


Channels **H94X** Aluminium (2000, 3000, 4000 & 6000mm lengths)
H94P Polypropylene (2000, 3000, 4000 & 6000mm lengths)
H94PSC Aluminium supporting channel and polypropylene (2000, 3000, 4000 & 6000mm lengths)




H550 - Track




H1A/550 - Bracket




H3S/550 - Bracket




H556 - Hanger




H556/52 - Hanger




H556/57 - Hanger




H94 - Channel



H104N/94 - Guide



H104NX/94 - Guide



H106HSS/94 - Guide

HENDERSON

