

MC540B



WINDOW HANDLE FRONT FIXING

RIGHT HANDED **VENTING**

CONTENTS

- 1 x Aria Venting Wedgeless right-handed window handle
- 2 x Screws
- 1 x Installation instructions

TOOLS REQUIRED



Drill



3.5mm drill bit



#1 square screwdriver



Marker pen



Safety goggles





The world's favourite lock

ASSA ABLOY New Zealand 6 Armstrong Road, Albany, Auckland 0632, New Zealand Quality, ISO 9001

Environmental, ISO 14001

For customer feedback: nzsales@assaabloy.com



ASSA ABLOY

ARIA VENTING WEDGELESS

Suitable for aluminium



Suitable for awning



Suitable for casement









An ASSA ABLOY Group brand




Aria Venting Window Handle the opposing tongue fastener



Fixing Instructions


Remove window fastener cover





Positioning fastener


Position fastener at desired location making sure that tongue has full engagement with the window frame as well as having enough clearance between the fastener base and the window frame; this will prevent the base clipping the frame when being opened.






Mark position

Turn handle approximately 30 degrees and using a black marker (or alternative tool) mark positions that holes are to be drilled. Now drill holes to suit screws using a 3.5mm drill bit (if replacing a handle, the existing holes should be sufficient).




Attach fastener

Using a square drive screwdriver attach the fastener to the sash using the two screws supplied.



Completing installation

Replace handle cover and check functionality of the handle and engagement of the tongue on the window frame.





The warranty covers manufacturing defects, standard finishes but excludes plated finishes or finishes exposed to a corrosive environment. The warranty excludes damage caused by installation contrary to written instructions and incidental or consequential damage. We recommend regular cleaning with mild detergent.